

## Thermal Receipt Printer

- The durable **CP-095** thermal printer offers embedded USB, RS232 and **10/100Mbps ethernet** communications capabilities for convenient printing in a wide variety of applications such as warehousing, inventory control, kitchen and field sales and service as well as medical and healthcare, point of sale, and test and measurement.
- With 203 dpi resolution at 260mm/s over a variable paper width of 80mm (3"), it delivers crisp and clear bar code labels as well as a wide range of printouts on standard paper stock.
- Resident firmware supports ranges of character sets, NV logo and fonts, error indications, and bar code formats that are printable horizontally or vertically (Driver mode).
- Software drivers are included from MS Windows 2000 to latest MS Windows 7 along with an OPOS/OLE library. The **CP-095** features the exclusive easy paper loading with wall-mounted function also.



**Built-in Ethernet connection**

## Features

- **Durable outer housing to protect against impact.**
- **Fast, simple EZ-OP paper loading.**
- **Built-in RS232, USB, Ethernet and cashdrawer connectors**
- **User friendly design**
- **Wide ranges of font, barcodes and character sets support**
- **Fast and High Performance:** Printing at 260mm/second helps you to handle more volume receipt tasks.
- **Reliable printer mechanism and compatibility:** Bundled with well-known brands printer mechanism to assure you of the printer reliability and compatibility.
- **Optional wall mounted ability:** More space with wall-mounted function from CP-095.

## Specifications

<b>Print method</b>	Line Thermal Printing
<b>Print width</b>	80mm: 72mm / 576dots & 64mm / 512 dots
<b>Dot pitch</b>	576dots/line & 512dots/line
<b>Printing speed</b>	260mm/s (65 lines/s)
<b>Paper</b>	79.5 +/- 0.5mm @ 83mm
<b>Cutter</b>	Full cut
<b>Resolutions</b>	200-203dpi
<b>Interfaces</b>	Built-in RS232, USB, Ethernet
<b>Indicator</b>	LED indicator
<b>Barcode symbologies</b>	EAN-8, EAN-13, UPC-A, UPC-E, JAN-13, Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128
<b>Drawer kick-out</b>	DC 12-24V / 1A, 2 Drawer
<b>Power supply</b>	DC 24V/2.5A Adapter with AC 110V / 220V, 50 -60 Hz
<b>Dimension</b>	140mm x 204mm x 145mm (W x D x H)
<b>Weight</b>	1.74Kg (w/o cable)
<b>Input buffer</b>	128Kbyte
<b>NV user memory</b>	256Kbyte
<b>Reliability</b>	100km
<b>Compatible</b>	ESC/POS
<b>Driver support</b>	Microsoft Windows 2000/XP/Vista/7 (32 & 64bit)